

MATERIAL SAFETY DATA SHEET

Section 1 - Material Identity	
Product Name SPOT REMOVER - #6209, SUPER FAST BODY SOLVENT- #6214	Product Use: CLEANING COMPOUND
Manufacturer(s) Supplier (s) Name & Address	Telephone Number: (215) 698-0500
ARDEX LABORATORIES, INC. 2050 BYBERRY ROAD PHILADELPHIA , PA 19116	Days: (215) 698-0500 Nights: CHEMTREC: 800/424-9300
DOT Proper Shipping Name Compounds, cleaning liquid (Containing Toluene and Petroleum Distillates), 3, UN1993, PGII	Super Fast may be reclassified in the US when shipping by ground or vessel as : Consumer Commodity ORM-D
FLAMMABLE	

Section 2 - Physical & Chemical Characteristics		
V.O.C.: 100 % by weight.	Solubility in Water by Weight: INSOLUBLE	Boiling Point: 231-300 DEG. F)
Appearance and Odor: CLEAR THIN LIQUID, AROMATIC PETROLEUM ODOR	Specific Gravity: 0.7-0.89 (@20 DEG. C)	Freezing Point -60 DEG. F
Vapor Pressure at 20EC: 11.6 (@20 DEG. C)	Percent Volatile by Volume: 100.00%	Evap. Rate (Butyl Acetate=1): 1.23

Section 3 -Ingredients & Specifications				
Materials	%	TLV	Hazard	CAS Number
VM&P NAPHTHA		300 ppm		64742-48-9
TOLUENE		100 ppm		108-88-3
Other components - NIL				

Section 4 - Fire & Explosion Hazard Data
Flash Point & Method: 54 DEG. F (CLOSED CUP)
Flammable Limits in Air % by volume: Lower: N/A Upper: N/A
Extinguishing Media: Any
Special Fire Fighting Procedures: N/A
Unusual Hazards: Flammable Liquid! Due to electrostatic accumulation hazards, containers and equipments must all be grounded. Material is highly volatile and gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

Section 5 - Health Hazard Data	
Route of Entry	a) Skin b) eyes:
Effects of Acute Exposure: HEALTH: 2 FLAMMABILITY: 3 PHYSICAL HAZARD: 0 PERSONAL PROTECTION: G	a) Skin Contact: MAY CAUSE MILD SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS, BURNING AND DRYING AND CRACKING OF THE SKIN.
	b) Eye Contact: ONE OR MORE COMPONENTS OF THIS MATERIAL IS AN EYE IRRITANT. DIRECT CONTACT WITH THE LIQUID OR EXPOSURE TO VAPORS OR MISTS MAY CAUSE STINGING, TEARING, REDNESS AND SWELLING.
	c) Swallowing: INGESTION OF EXCESSIVE QUANTITIES MAY CAUSE: IRRITATION OF THE DIGESTIVE TRACT, SIGNS OF NERVOUS SYSTEM DEPRESSION (E.G., HEADACHE, DROWSINESS, DIZZINESS, LOSS OF CONCENTRATION AND FATIGUE.)
	d) Skin Absorption: PROMPTLY FLUSH AREA WITH WATER. REMOVE CLOTHING IF PRESENT. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

*	e) Inhalation: THIS MATERIAL HAS A LOW DEGREE OF TOXICITY BREATHING HIGH LEVEL OF VAPORS OR MISTS MAY CAUSE: IRRITATION OF THE NOSE AND THROAT, SIGNS OF NERVOUS SYSTEM DEPRESSION (E.G., HEADACHE, DROWSINESS, DIZZINESS, LOSS OF CONCENTRATION & FATIGUE.).
Chronic Effects of Overexposure:	EXPOSURE TO HIGH LEVEL OF THIS MATERIAL (E.G., IN ENCLOSED SPACES OR WITH DELIBERATE ABUSE) MAY BE ASSOCIATED WITH CARDIAC ARRHYTHMIAS. EPINEPHRINE AND OTHER SYMPATHOMIMETIC DRUGS MAY INITIATE CARDIA ARRHYTHMIAS.
Other Health Hazards:	N/A
Emergency and First Aid Procedures:	a) Skin: PROMPTLY WASH AFFECTED AREA WITH MILD SOAP AND WATER. REMOVE CLOTHING IF PRESENT. IF IRRITATION OR REDNESS PERSISTS GET MEDICAL ATTENTION.
	b) Eyes: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES, LIFTING UPPER AND LOWER LIDS OCCASIONALLY. GET MEDICAL ATTENTION. CONTACT LENSES SHOULD NOT BE WORN WHEN WORKING WITH THIS CHEMICAL.
	c) Swallowing: IF THE PERSON IS CONSCIOUS, GIVE LARGE QUANTITIES OF WATER TO DILUTE. DO NOT ATTEMPT TO INDUCE VOMITING. GET MEDICAL ATTENTION.
	d) Inhalation: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP THE AFFECTED PERSON WARM AND AT REST. GET MEDICAL ATTENTION AS SOON AS POSSIBLE.

Carcinogen Evaluation N/A

Section 6 - Reactivity Data

Stability -	Yes
Conditions to Avoid for Stability	See below
Incompatibility (Materials to Avoid) -	VAPORS forms combustible / explosive mixtures with air. Avoid strong acids or bases, oxidizing agents & selected amines.
Hazardous Polymerization -	Will not occur
Hazardous Decomposition/Byproducts	Carbon Monoxide and/or Carbon Dioxide.

Section 7 - Spill or Leak Procedures

Release/Spill Procedures	VENTILATE AREA. ABSORB INTO NON-REACTIVE MEDIA SUCH AS DIATOMACEOUS EARTH OR VERMICULITE; SWEEP INTO NON-REACTIVE VESSEL (I.E., STEEL DRUM OR PAIL)
	WASTE DISPOSAL METHOD: DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

Section 8 - Special Protection Information

Protective Equipment	Eyes: USE DUST-AND SPLASH-PROOF SAFETY GOGGLES WHERE THERE IS ANY POSSIBILITY OF LIQUID, MIST OR DUST CONTACTING THE EYES.
	Respirator: RECOMMENDED; DUST MASK
	Gloves: WEAR IMPERMEABLE GLOVES (BUTYL OR HEAVY VINYL LATEX TYPE)
Ventilation	Other: PROTECTIVE EQUIPMENT – IF POSSIBILITY EXISTS FOR SPLASHING WEAR FACEGUARDS WITH SIDE SHIELDS. USE RESPIRATOR WHEN WORKING IN A TOTALLY CLOSED SYSTEM
	General Mechanical: None required
	Other: USE IN A WELL VENTILATED AREA

Section 9 - Special Precautions

Handling & Storage	General: N/A
	Other:

Section 10 - Other Information

The information contained herein is based on data considered accurate. However, the information is provided without any warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility for personal injury or property damage to vendees, users or third parties caused by the material. We also do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

Prepared By:

ARDEX LABORATORIES, INC.

New/Revision Date: 03/14/05