Premium Plus ® Interior Flat Enamel -PastelBase No. 1855

1855

REND

Process Corporation 3400 W. Segerstrom Avenue Santa Ana, CA 92704 (714) 545-

7101 (714) 241-

(714) 241-1002 (800) 854-0133 ext. 2 Health Hazard 1

Fire Hazard 1

Reactivity 0

Personal Protection

**HMIS** 

**NFPA** 

0

For emergencies in the US, call CHEMTREC: 800-424-9300 In Canada, call CANUTEC: (613) 996-6666 (call

collect)

# SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Non hazardous ingredient(s)	Not applicable	30 - 60 by weight
2-ethylhexyl benzoate	5444-75-7	1 - 5 by weight
Acrylic polymer	No Data	10 - 30 by weight
Silica, crystalline - cristobalite	14464-46-1	0.1 - 1 by weight
Nepheline Syenite	37244-96-5	10 - 30 by weight
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5 by weight
Titanium dioxide	13463-67-7	10 - 30 by weight

Ethylene glycol 107-21-1 1 - 5 by weight

#### SECTION 3: HAZARDS IDENTIFICATION

Irritant.

### fects:

May cause irritation.

May cause irritation.

Prolonged or excessive inhalation may cause respiratory tract irritation.

May be harmful if swallowed. May cause vomiting.

Prolonged or repeated contact may cause skin irritation.

Overexposure may cause headaches and dizziness.

Eyes. Skin. Respiratory system. Digestive system.

None generally recognized.

### SECTION 4: FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symp

of overexposure persists.

Skin Contact: Immediately wash skin with soap and plenty of water.

Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personne

immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give any

by mouth to an unconscious person.

Other First Aid: Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dil

material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspi

#### SECTION 5: FIRE FIGHTING MEASURES

Flash Point: No Data

Lower Flammable/Explosive Limit: Not applicable.

Upper Flammable/Explosive Limit: Not applicable.

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving

material.

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and

protective gear.

NFPA Ratings:

NFPA Health: 1
NFPA Flammability: 1
NFPA Reactivity: 0

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use proper personal protective equipment as listed in Section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Spill Cleanup Measures: Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide

ventilation. Clean up spills immediately observing precautions in the protective equipment section.

#### SECTION 7: HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Storage: Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible

substances. Keep container tightly closed when not in use.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

### SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be

sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local

procedures for selection, training, inspection and maintenance of the personal protective equipment.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face

protection regulation, or the European standard EN 166.

Skin Protection Description: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used

prevent contact with eyes, skin or clothing.

Wear appropriate protective gloves. Consult glove manufacturer's data for permeability data.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible un

certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection proviby air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential funcontrolled release, exposure levels are not known, or any other circumstances where air purifying respirat

may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

#### **EXPOSURE GUIDELINES**

Silica, crystalline - cristobalite :

Guideline ACGIH: TLV-TWA: 0.05 mg/m3 (Respirable)

Guideline OSHA: OSHA-TWA: One half the Quartz PEL [30 mg/m3]/{% Sio2} + 2]

Silica, amorphous, precipitated and gel:

Guideline ACGIH: TLV-TWA: 10 mg/m3
Guideline OSHA: OSHA-TWA: 20 mg/m3

<u>Titanium dioxide</u>:

Guideline ACGIH: TLV-TWA: 10 mg/m3
Guideline OSHA: OSHA-TWA: 15 mg/m3

Ethylene glycol:

Melting Point:

Guideline ACGIH: TLV-STEL: C 100 mg/m3 (Aerosol only)

No Data

#### SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid.

Color: White

Boiling Point: No Data

Density: 10 - 12 Lbs./gal.

Vapor Density: Greater than 1 (Air = 1). Vapor Pressure: Greater than 1 (Air = 1). pH: 8.5 to 9.5

Molecular Formula: Mixture

Molecular Weight: Mixture

Flash Point: No Data

VOC Content: Material VOC: 41 gm/l (Includes Water)

Coating VOC.: 96 gm/l (Excludes Water)

### SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Hazardous Polymerization: Not reported.

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

Special Decomposition Products: Incomplete combustion may produce carbon monoxide and other toxic gases.

### SECTION 11: TOXICOLOGICAL INFORMATION

Silica, crystalline - cristobalite :

RTECS Number: VV7325000

Carcinogenicity: IARC: Group 1: Carcinogenic to humans. NTP: Reasonably anticipated to be a human carcinogen.

Silica, amorphous, precipitated and gel:

RTECS Number: VV7315000

<u>Titanium dioxide</u>:

RTECS Number: XR2275000

Skin - Rabbit; Standard Draize test. : 300 ug/3D; (Intermittent) mild. (RTECS)

Ingestion: Ingestion - Rat TDLo: 60 gm/kg; Gastrointestinal - Hypermotility, diarrhea Gastrointestinal - Other changes.

(RTECS)

Carcinogenicity: IARC: Group 2B: Possibly carcinogenic to humans.

#### **Ethylene glycol:**

RTECS Number: KW2975000

Eye: Eye - Rabbit; Standard Draize test. : 500 mg/24H; mild.

Eye - Rabbit; Standard Draize test.: 1440 mg/6H; Moderate. (RTECS)

Skin: Skin - Rabbit; Open irritation test: 555 mg; mild. (RTECS)

Inhalation: Inhalation - Rat LC: >200 mg/m3/4H; Details of toxic effects not reported other than lethal dose value

Inhalation - Mouse LC: >200 mg/m3/2H; Details of toxic effects not reported other than lethal dose value (R

Ingestion: Ingestion - Rat LD50: 4700 mg/kg; Details of toxic effects not reported other than lethal dose value. (RTECS

#### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

### SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to er

compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

### SECTION 14: TRANSPORT INFORMATION

DOT UN Number: No Data

DOT Hazard Class: No Data

### SECTION 15: REGULATORY INFORMATION

California PROP 65: WARNING: This product contains a chemical known to the state of California to cause cancer and birth defect

other reproductive harm.

2-ethylhexyl benzoate:

TSCA Inventory Status: Listed

Canada DSL: Listed

Silica, crystalline - cristobalite:

TSCA Inventory Status: Listed

State Regulations: Listed in the New Jersey State Right to Know List.

Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL: Listed

**Nepheline Syenite:** 

TSCA Inventory Status: Not listed

Canada DSL: Listed

Silica, amorphous, precipitated and gel:

TSCA Inventory Status: Not listed

Canada DSL: Listed

**<u>Titanium dioxide</u>**:

TSCA Inventory Status: Listed

State Regulations: Listed in the New Jersey State Right to Know List.

Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL: Listed

**Ethylene glycol:** 

TSCA Inventory Status: Listed

State Regulations: Listed in the New Jersey State Right to Know List.

Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL: Listed

## **SECTION 16: ADDITIONAL INFORMATION**

**HMIS Ratings**:

HMIS Health Hazard: 1
HMIS Fire Hazard: 1
HMIS Reactivity: 0
HMIS Other: x

SDS Creation Date: January 30, 2007
SDS Revision Date: December 30, 2011

MSDS Revision Notes: "Quarterly formula update"

SDS Format: According to ANSI Z400.1-2004

MSDS Author: Actio Corporation

Disclaimer: This Health and Safety Information is correct to the best of our knowledge and belief at the date of its public

but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have d supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarant specific properties. All chemicals should be handled only by competent personnel, within a controlled environ Should further information be required, this can be obtained through the sales office whose address is at the

this data sheet.

Trademark: The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered tradem

BEHR Process Corporation. All Rights Reserved.

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.