



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** White Lithium Grease

**Other means of identification**

**Product code** 03080

**Recommended use** Lubricating grease

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service**

**24-Hour Emergency (CHEMTREC)** 800-272-4620

703-527-3887 (US)

703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

|                              |  |                             |
|------------------------------|--|-----------------------------|
| <b>Physical hazards</b>      | Flammable aerosols                                     | Category 1                  |
|                              | Gases under pressure                                   | Liquefied gas               |
| <b>Health hazards</b>        | Skin corrosion/irritation                              | Category 2                  |
|                              | Carcinogenicity  | Category 2                  |
|                              | Reproductive toxicity (fertility)                      | Category 2                  |
|                              | Specific target organ toxicity, single exposure        | Category 3 narcotic effects |
|                              | Specific target organ toxicity, repeated exposure      | Category 2                  |
|                              | Aspiration hazard                                      | Category 1                  |
| <b>Environmental hazards</b> | Hazardous to the aquatic environment, acute hazard     | Category 3                  |
|                              | Hazardous to the aquatic environment, long-term hazard | Category 3                  |
| <b>OSHA defined hazards</b>  | Not classified.  |                             |

**Label elements**



**Signal word**

Danger

**Hazard statement**

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility. May cause damage to organs (nervous system, upper respiratory tract, skin, eyes) through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical attention.

### Storage

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

### Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

### Hazard(s) not otherwise classified (HNOC)

None known.

## 3. Composition/information on ingredients

---

### Mixtures

| Chemical name  | Common name and synonyms | CAS number | %       |
|--|--------------------------|------------|---------|
| Liquefied Petroleum Gas                                |                          | 68476-86-8 | 30 - 40 |
| Naphtha (petroleum), hydrotreated light                |                          | 64742-49-0 | 30 - 40 |
| Distillates (petroleum), hydrotreated heavy naphthenic |                          | 64742-52-5 | 10 - 20 |
| 2-Methylpentane  |                          | 107-83-5   | 5 - 10  |
| n-Hexane   |                          | 110-54-3   | 1 - 3   |
| Titanium dioxide                                       |                          | 13463-67-7 | < 1     |
| Zinc oxide   |                          | 1314-13-2  | < 1     |
| Calcium bis(dinonylnaphthalenesulphonate)              |                          | 57855-77-3 | < 0.2   |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

---

|   |  |
|---|--|
| <b>Inhalation</b>   | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.  |
| <b>Skin contact</b>   | Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.  |
| <b>Eye contact</b>  | Rinse with water. Get medical attention if irritation develops and persists.   |
| <b>Ingestion</b>  | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.  |
| <b>Most important symptoms/effects, acute and delayed</b>                     | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.                 |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.   |
| <b>General information</b>  | IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. |

## 5. Fire-fighting measures

---

**Suitable extinguishing media** Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

|  |  |
|--|--|
| <b>Unsuitable extinguishing media</b>                                | None known.  |
| <b>Specific hazards arising from the chemical</b>                    | Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.                  |
| <b>Special protective equipment and precautions for firefighters</b> | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| <b>Fire-fighting equipment/instructions</b>                          | In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.          |
| <b>General fire hazards</b>  | Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.   |

## 6. Accidental release measures

|  |   |
|--|---|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust/fume/gas/mist/vapors/spray. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| <b>Methods and materials for containment and cleaning up</b>               | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.  |
| <b>Environmental precautions</b>   | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.  |

## 7. Handling and storage

|   |  |
|---|--|
| <b>Precautions for safe handling</b>                                | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, please see the product label. |
| <b>Conditions for safe storage, including any incompatibilities</b> | Level 3 Aerosol.<br><br>Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).  |

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components  | Type | Value  | Form        |
|---|------|--|-------------|
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) | PEL  | 5 mg/m3  | Mist.       |
| n-Hexane (CAS 110-54-3)   | PEL  | 2000 mg/m3<br>500 ppm<br>1800 mg/m3<br>500 ppm |             |
| Titanium dioxide (CAS 13463-67-7)                                       | PEL  | 15 mg/m3                                       | Total dust. |

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components                 | Type | Value    | Form                 |
|----------------------------|------|----------|----------------------|
| Zinc oxide (CAS 1314-13-2) | PEL  | 5 mg/m3  | Respirable fraction. |
|                            |      | 5 mg/m3  | Fume.                |
|                            |      | 15 mg/m3 | Total dust.          |

**US. ACGIH Threshold Limit Values**

| Components  | Type | Value    | Form                 |
|---|------|----------|----------------------|
| 2-Methylpentane (CAS 107-83-5)  | STEL | 1000 ppm |                      |
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) | TWA  | 500 ppm  | Inhalable fraction.  |
|   | TWA  | 5 mg/m3  |                      |
| n-Hexane (CAS 110-54-3)   | TWA  | 50 ppm   |                      |
| Titanium dioxide (CAS 13463-67-7)                                       | TWA  | 10 mg/m3 |                      |
| Zinc oxide (CAS 1314-13-2)  | STEL | 10 mg/m3 | Respirable fraction. |
|   | TWA  | 2 mg/m3  | Respirable fraction. |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components  | Type    | Value      | Form  |
|---|---------|------------|-------|
| 2-Methylpentane (CAS 107-83-5)  | Ceiling | 1800 mg/m3 |       |
|   |         | 510 ppm    |       |
|   |         | 350 mg/m3  |       |
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) | Ceiling | 100 ppm    |       |
|   |         | 1800 mg/m3 |       |
|   |         | 10 mg/m3   | Mist. |
| n-Hexane (CAS 110-54-3)   | TWA     | 5 mg/m3    | Mist. |
|   |         | 180 mg/m3  |       |
|   |         | 50 ppm     |       |
| Zinc oxide (CAS 1314-13-2)  | Ceiling | 15 mg/m3   | Dust. |
|   |         | 10 mg/m3   | Fume. |
|   |         | 5 mg/m3    | Fume. |
|   |         | 5 mg/m3    | Dust. |

**Biological limit values**

**ACGIH Biological Exposure Indices**

| Components              | Value    | Determinant                         | Specimen | Sampling Time |
|-------------------------|----------|-------------------------------------|----------|---------------|
| n-Hexane (CAS 110-54-3) | 0.4 mg/l | 2,5-Hexanedio n, without hydrolysis | Urine    | *             |

\* - For sampling details, please see the source document.

**Exposure guidelines**

**US - California OELs: Skin designation**

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

## Individual protection measures, such as personal protective equipment

|                                       |  |
|---------------------------------------|--|
| <b>Eye/face protection</b>            | Wear safety glasses with side shields (or goggles).  |
| <b>Skin protection</b>                |  |
| <b>Hand protection</b>                | Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton®.   |
| <b>Other</b>                          | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.   |
| <b>Respiratory protection</b>         | If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels. |
| <b>Thermal hazards</b>                | Wear appropriate thermal protective clothing, when necessary.  |
| <b>General hygiene considerations</b> | When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.  |

---

## 9. Physical and chemical properties

### Appearance

|   |                                    |
|---|------------------------------------|
| <b>Physical state</b>                               | Solid.                             |
| <b>Form</b>   | Aerosol. Grease.                   |
| <b>Color</b>  | Off-white.                         |
| <b>Odor</b>   | Solvent.                           |
| <b>Odor threshold</b>                               | Not available.                     |
| <b>pH</b>   | Not available.                     |
| <b>Melting point/freezing point</b>                 | -244.7 °F (-153.7 °C) estimated    |
| <b>Initial boiling point and boiling range</b>      | 118.4 °F (48 °C) estimated         |
| <b>Flash point</b>                                  | < 0 °F (< -17.8 °C) Tag Closed Cup |
| <b>Evaporation rate</b>                             | Fast.                              |
| <b>Flammability (solid, gas)</b>                    | Not available.                     |
| <b>Upper/lower flammability or explosive limits</b> |                                    |
| <b>Flammability limit - lower (%)</b>               | 1 % estimated                      |
| <b>Flammability limit - upper (%)</b>               | 8 % estimated                      |
| <b>Vapor pressure</b>                               | 2217.9 hPa estimated               |
| <b>Vapor density</b>                                | > 1 (air = 1)                      |
| <b>Relative density</b>                             | 0.64 estimated                     |
| <b>Solubility (water)</b>                           | Insoluble.                         |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available.                     |
| <b>Auto-ignition temperature</b>                    | 437 °F (225 °C) estimated          |
| <b>Decomposition temperature</b>                    | Not available.                     |
| <b>Viscosity (kinematic)</b>                        | Not available.                     |
| <b>Percent volatile</b>                             | 84.9 % estimated                   |

---

## 10. Stability and reactivity

|   |   |
|---|---|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.   |
| <b>Possibility of hazardous reactions</b> | No dangerous reaction known under conditions of normal use.                                   |
| <b>Conditions to avoid</b>                | Heat, flames and sparks. Contact with incompatible materials.                                 |
| <b>Incompatible materials</b>             | Strong oxidizing agents. Chlorine.  |
| <b>Hazardous decomposition products</b>   | Carbon oxides.  |

## 11. Toxicological information

### Information on likely routes of exposure

|                     |  |
|---------------------|--|
| <b>Ingestion</b>    | Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.                           |
| <b>Inhalation</b>   | May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. |
| <b>Skin contact</b> | Causes skin irritation.  |
| <b>Eye contact</b>  | Direct contact with eyes may cause temporary irritation.   |

**Symptoms related to the physical, chemical and toxicological characteristics** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

| Product              | Species | Test Results   |
|----------------------|---------|--|
| White Lithium Grease |         |  |
| <b>Acute</b>         |         |  |
| <i>Dermal</i>        |         |  |
| LD50                 | Rabbit  | 3913.0442 mg/kg estimated  |
| <i>Inhalation</i>    |         |  |
| LC50                 | Rat     | 88578.8594 ppm, 4 hours estimated<br>82.9611 mg/l, 4 hours estimated |
| <i>Oral</i>          |         |  |
| LD50                 | Rat     | 6327.0615 mg/kg estimated  |

\* Estimates for product may be based on additional component data not shown.

|   |   |
|---|---|
| <b>Skin corrosion/irritation</b>                              | Causes skin irritation.   |
| <b>Serious eye damage/eye irritation</b>                      | Direct contact with eyes may cause temporary irritation.  |
| <b>Respiratory sensitization</b>                              | Not available.  |
| <b>Skin sensitization</b>                                     | This product is not expected to cause skin sensitization.   |
| <b>Germ cell mutagenicity</b>                                 | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.  |
| <b>Carcinogenicity</b>  | Suspected of causing cancer.  |
| <b>IARC Monographs. Overall Evaluation of Carcinogenicity</b> |   |
| Titanium dioxide (CAS 13463-67-7)                             | 2B Possibly carcinogenic to humans.   |
| <b>Reproductive toxicity</b>                                  | Suspected of damaging fertility.  |
| <b>Specific target organ toxicity - single exposure</b>       | May cause drowsiness and dizziness.   |
| <b>Specific target organ toxicity - repeated exposure</b>     | May cause damage to organs through prolonged or repeated exposure.  |
| <b>Aspiration hazard</b>                                      | May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. |
| <b>Chronic effects</b>  | Prolonged exposure may cause chronic effects. May cause damage to organs through prolonged or repeated exposure.  |

## 12. Ecological information

| <b>Ecotoxicity</b>   | Harmful to aquatic life with long lasting effects. |         |                                  |
|----------------------|--|---------|----------------------------------|
| Product              | Species  |         | Test Results                     |
| White Lithium Grease |  |         |                                  |
| <b>Aquatic</b>       |  |         |                                  |
| <i>Acute</i>         |  |         |                                  |
| Crustacea            | EC50   | Daphnia | 21.9728 mg/l, 48 hours estimated |
| Fish                 | LC50   | Fish    | 246.6337 ppm, 96 hours estimated |

| Components  | Species |   | Test Results                 |
|---|---------|---|------------------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) |         |   |                              |
| <b>Aquatic</b>  |         |   |                              |
| Crustacea   | EC50    | Water flea (Daphnia magna)                          | 1000 mg/l, 48 hours          |
| Fish  | LC50    | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 5000 mg/l, 96 hours          |
| n-Hexane (CAS 110-54-3)   |         |   |                              |
| <b>Aquatic</b>  |         |   |                              |
| Fish  | LC50    | Fathead minnow (Pimephales promelas)                | 2.101 - 2.981 mg/l, 96 hours |
| Titanium dioxide (CAS 13463-67-7)                                       |         |   |                              |
| <i>Acute</i>  |         |   |                              |
| Other   | EC50    | Pseudokirchnerella subcapitata                      | 5.83 mg/l, 72 hours          |
| <i>Chronic</i>  |         |   |                              |
| Other   | NOEC    | Pseudokirchnerella subcapitata                      | 0.984 mg/l, 72 hours         |
| <b>Aquatic</b>  |         |   |                              |
| <i>Acute</i>  |         |   |                              |
| Crustacea   | LC50    | Ceriodaphnia dubia                                  | 3 mg/l, 48 hours             |
|   |         | Water flea (Daphnia magna)                          | 5.5 ppm, 48 hours            |
| Fish  | LC50    | Fathead minnow (Pimephales promelas)                | 1000 mg/l, 96 hours          |
| Zinc oxide (CAS 1314-13-2)  |         |   |                              |
| <b>Aquatic</b>  |         |   |                              |
| <i>Acute</i>  |         |   |                              |
| Crustacea   | EC50    | Water flea (Daphnia magna)                          | 0.098 mg/l, 48 hours         |
| Fish  | LC50    | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 1.1 ppm, 96 hours            |

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

2-Methylpentane 3.74

n-Hexane 3.9

**Bioconcentration factor (BCF)**

Titanium dioxide 352

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal of waste from residues / unused products** If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

### 14. Transport information

**DOT**

**UN number** UN1950

**UN proper shipping name** Aerosols, flammable, Limited Quantity

**Transport hazard class(es)**

**Class** 2.1

**Subsidiary risk** -



|                                     |   |
|-------------------------------------|---|
| <b>Label(s)</b>                     | 2.1   |
| <b>Packing group</b>                | Not applicable.   |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Special provisions</b>           | N82   |
| <b>Packaging exceptions</b>         | 306   |
| <b>Packaging non bulk</b>           | None  |
| <b>Packaging bulk</b>               | None  |

#### IATA

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1950  |
| <b>UN proper shipping name</b>      | Aerosols, flammable, Limited Quantity                                   |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 2.1   |
| <b>Subsidiary risk</b>              | -   |
| <b>Packing group</b>                | Not applicable.   |
| <b>Environmental hazards</b>        | No.   |
| <b>ERG Code</b>                     | 10L   |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Other information</b>            |   |
| <b>Passenger and cargo aircraft</b> | Allowed.  |
| <b>Cargo aircraft only</b>          | Allowed.  |

#### IMDG

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | UN1950  |
| <b>UN proper shipping name</b>      | AEROSOLS, LIMITED QUANTITY  |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>                        | 2   |
| <b>Subsidiary risk</b>              | -   |
| <b>Packing group</b>                | Not applicable.   |
| <b>Environmental hazards</b>        |   |
| <b>Marine pollutant</b>             | No.   |
| <b>EmS</b>                          | Not available.  |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

#### **TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

#### **SARA 304 Emergency release notification**

Not regulated.

#### **US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

#### **US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

n-Hexane (CAS 110-54-3)

Zinc oxide (CAS 1314-13-2)

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

n-Hexane (CAS 110-54-3)

Zinc oxide (CAS 1314-13-2)

#### **CERCLA Hazardous Substances: Reportable quantity**

n-Hexane (CAS 110-54-3)

5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

#### **Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

n-Hexane (CAS 110-54-3)

#### **Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.



**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Section 311/312 Hazard categories**  
Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**US state regulations**

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. New Jersey Worker and Community Right-to-Know Act**

2-Methylpentane (CAS 107-83-5)  
Titanium dioxide (CAS 13463-67-7)  
n-Hexane (CAS 110-54-3)  
Zinc oxide (CAS 1314-13-2)

**US. Massachusetts RTK - Substance List**

2-Methylpentane (CAS 107-83-5)  
n-Hexane (CAS 110-54-3)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Zinc oxide (CAS 1314-13-2)  
2-Methylpentane (CAS 107-83-5)  
n-Hexane (CAS 110-54-3)  
Titanium dioxide (CAS 13463-67-7)

**US. Rhode Island RTK**

n-Hexane (CAS 110-54-3)  
Zinc oxide (CAS 1314-13-2)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011

**Volatile organic compounds (VOC) regulations**

**EPA**

**VOC content (40 CFR 51.100(s))** 100 %

**Consumer products (40 CFR 59, Subpt. C)** Not regulated

**State**

**Consumer products** Not regulated (semi-solid lubricant)

**VOC content (CA)** 84.7 %

**VOC content (OTC)** 84.7 %


**International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | Yes                    |
| Canada               | Domestic Substances List (DSL)   | Yes                    |
| Canada               | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | Yes                    |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes                    |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                | Existing Chemicals List (ECL)  | Yes                    |

| Country(s) or region        | Inventory name  | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| New Zealand                 | New Zealand Inventory   | Yes                    |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes                    |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                     | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

|                     |   |
|---------------------|---|
| Issue date          | 01-16-2015  |
| Prepared by         | Allison Cho   |
| Version #           | 01  |
| Further information | CRC # 568F/G  |
| HMIS® ratings       | Health: 2*<br>Flammability: 4<br>Physical hazard: 0<br>Personal protection: B     |
| NFPA ratings        | Health: 2<br>Flammability: 4<br>Instability: 0                                    |
| NFPA ratings        |  |

**Disclaimer**

CRC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.