

Accolade™

SEALER/FINISH

PRODUCT DESCRIPTION:

Accolade™ is a versatile sealer/finish which has been formulated to protect a wide variety of non-resilient and resilient flooring materials. By blending acrylic polymer elements fortified with urethane, Franklin has combined the properties of a top quality sealer with those of a superior floor finish.

FEATURES:

Versatility:

Accolade™ simplifies floor care by providing effective sealing of porous/old floors and providing an above average gloss with a single product.

Exceptional Gloss:

Accolade's™ improved urethane formula provides "finish" like gloss and depth compared to traditional sealer/finish formulas.

Repairable:

Accolade™ will stand up to high speed burnishing and frequent detergent scrubbing.

Clear Film:

Accolade™ dries to a clear film and is specifically formulated to not yellow over time.

PRODUCT SPECIFICATIONS:

pH	8.6 ± 0.2
Appearance	Opaque White Emulsion
Fragrance	Polymeric
Freezing Point	About 32°F
% Non-Volatile Solids	19.5 ± 0.5
% Total Solids	25.4
Boiling Point	212°F
Solubility in Water	Dispersible
Flash Point	None
Coverage	1700 to 2000 sq. ft. per gallon (may vary due to differences in porosity of the surface)

Slip Resistance: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water	7732-18-5
Styrene acrylic polymer	25085-34-1
Diethylene glycol monoethyl ether	111-90-0
Polypropylene emulsion	Mixture
Tri-butoxyethyl phosphate	78-51-3

DILUTIONS	HEALTH	FLAMMABILITY	REACTIVITY
CONCENTRATE	NFPA 1	NFPA 0	NFPA 0
CONCENTRAR	HMS 1	HMS 0	HMS 0
PROPORCIÓN	SALUD	INFLAMABILIDAD	REACTIVIDAD

0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Mínimo	Mínimo	Moderar	Grave	Drástico

DATA TECH SHEET

Accolade™ SEALER/FINISH

DIRECTIONS

USE INFORMATION

Before applying **Accolade™** remove old finish and sealer from floor using appropriate Franklin stripper and following label directions. Can be used on terrazzo, quarry tile, brick, unglazed ceramic, Mexican tile, slate, unpolished marble and all types of resilient flooring.

INITIAL APPLICATION




CAUTION




1. REMOVE



2. APPLY




3. DRY
30-60




4. APPLY

MAINTENANCE



1. DUST MOP



2. MOP

INITIAL APPLICATION

1. **REMOVE** old sealer/finish following label directions using an appropriate Franklin stripper.
2. **APPLY** a thin coat of **Accolade™** using a clean finish mop.
3. **DRY:** Allow 30-60 minutes drying time.
4. **APPLY** 3-4 additional coats. For best results allow adequate drying time between coats.

MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels and other attached soils with a long-handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a Franklin cleaner, following the label directions.

WARNING: May cause eye, skin and respiratory tract irritation.

Hazard Statement

Harmful to aquatic life.

Precautionary Statement

Avoid release to the environment.

Response

Wash hands after handling.

Storage

Store away from incompatible materials.

Disposal

Dispose of contents / container in accordance with local / regional / national / international regulations.

KEEP OUT OF REACH OF CHILDREN.

PERSONAL PROTECTION:

Respiratory Protection: Not needed in normal use of this product.

Ventilation: Use with adequate ventilation.

Eye Protection: Safety glasses are optional.

Protective Gloves: Protective gloves are optional.

Other Protective Clothing or Equipment: Wear clothing as necessary to prevent skin contact.

TRANSPORTATION INFORMATION:

U.S. DOT - Proper Shipping Name: Not regulated by DOT.

Marine Pollutant: No

© FULLER COMMERCIAL PRODUCTS - 2014

One Fuller Way
Great Bend, KS 67530
United States
www.fullercommercial.com

Customer Service (800) 848-4901
CHEMTREC (800) 424-9300
Emergency (620) 792-1711
24 Hour Emergency (800) 424-9300

F1390TDS-0714